

In compliance with the following Council Directives

1999/5/EC: R&TTE Directive
2006/95/EC: Low Voltage Directive
2004/108/EC: EMC Directive
2002/95/EC: RoHS Directive

We, manufacturer: **BEA SA**
LIEGE Science Park
Allée des Noisetiers 5
B-4031 ANGLEUR
Belgium



declare under our sole responsibility that the following product(s)

EAS RF Receiver
 Key Fob transmitter
 Push Plate transmitter 3V
 Push Plate transmitter 9V

to which this declaration relates are in conformity with the relevant provisions of the following standard(s) or other normative document(s):

EN 300 220-2 2000-09	Electromagnetic compatibility and Radio spectrum Matters (ERM); Short Range Devices (SRD); Radio equipment to be used in the 25 MHz to 1 000 MHz frequency range with power levels ranging up to 500 mW Part 2: Supplementary parameters not intended for conformity purposes
EN 301 489 -1 2007-04	Electromagnetic compatibility and Radio spectrum Matters (ERM)
EN 301 489 -3 2002-04	Electromagnetic Compatibility (EMC) standard for radio equipment and services Part 1: Common technical requirements Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 40 GHz.
EN 60950-1 2005-12	Information Technology Equipment – Safety Part 1: General Requirements

The technical information is maintained at BEA SA and includes the following document(s):

Technical Construction File N° TCF063

We, the undersigned, hereby declare that the equipment specified above conforms to the above Council Directive(s) and Standard(s).

Manufacturer:

Signature:

Name: Philippe VAN GENECHTEN
 Position: General Manager
 Date: August, 2008

Signature:

Name: Yves BORLEZ
 Position: Research & Development Manager
 Date: August, 2008

EAS RF

ADDITIONAL PRODUCT INFORMATION

IMPORTANT INFORMATION CONCERNING THE USE OF THE TRANSMITTERS

- Characteristics key fob transmitter:

Transmitter frequency:	433 MHz $\pm$ 0.1MHz
Operating voltage:	3 V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C

- Characteristics transmitter for push plates 3V:

Transmitter frequency:	433 MHz $\pm$ 0.1MHz
Operating voltage:	3 V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C

- Characteristics transmitter for push plates 9V:

Transmitter frequency:	433 MHz $\pm$ 0.1MHz
Operating voltage:	9V
Operating current:	3 mA typ.
Operating temperature range:	-10°C to +55°C