



MODELO	CARACTERÍSTICAS							EUROS
	KW	HP	CARGA AXIAL	TENSIÓN	AMP.	L mm	PESO kg	
19090	30	40	45000N	400V	61	925	145	5.133 €
19091	37	50	45000N	400V	74	1000	157	5.517 €
19092	45	60	45000N	400V	89	1077	172	5.965 €
19093	55	75	45000N	400V	108	1.394	202	6.757 €
19095	75	100	45000N	400V	145	1.496	240	8.497 €
19096	93	125	45000N	400V	190	1.748	318	11.218 €
19097	110	150	45000N	400V	222	1.906	381	13.565 €
19098	130	175	45000N	400V	252	2.179	420	15.187 €
19099	150	200	45000N	400V	284	2.408	494	18.807 €

MODELO	CARACTERÍSTICAS							EUROS
	KW	HP	CARGA AXIAL	TENSIÓN	AMP.	L mm	PESO kg	
19110	30	40	45000N	400V	61	925	145	5.588 €
19111	37	50	45000N	400V	74	1000	157	5.972 €
19112	45	60	45000N	400V	89	1077	172	6.420 €
19113	55	75	45000N	400V	108	1.394	202	7.353 €
19114	75	100	45000N	400V	145	1.496	240	9.093 €
19115	93	125	45000N	400V	190	1.748	318	11.814 €
19116	110	150	45000N	400V	222	1.906	381	14.271 €
19117	130	175	45000N	400V	252	2.179	420	15.893 €
19118	150	200	45000N	400V	284	2.408	494	19.513 €

38.10
38.07

42.93
MIN.
FULL
SPLINE

5.10

CHECK
VALVE

M8 X 31.75 - 6G
GROUND SCREW

max. ϕ 190.5

PULS. B. (250/0.76)
FREE END PLAN

101.59
101.59

38.1
38.07

42.93
MIN FULL
SPLINE

6.10

101.5
PLUS 0.008/0.203
FREE DIA PLAY

CHECK VALVE

M8 X 1.25 - 60

195.6 MAX.

N EN ALTERNANCIA N DE VELOCIDAD



PÁGINA
373



PÁGINA
376



PÁGINA
380



PÁGINA
377

ALPOMPE